


**Specifications / Špecifikácia**

<b>Model</b>	PLA K
<b>Power / Výkon</b>	36 W
<b>Luminous Flux/Svetelný tok</b>	3840 LM
<b>Color temperature / farba</b>	4000K
<b>Electrical class / el. tried</b>	II
<b>UGR</b>	16
<b>Color Rendering Index (CRI)</b>	Ra 80
<b>Beam angle Uhol vyžarovania</b>	100°
<b>Input Voltage Napájanie</b>	200-240VAC
<b>Power Factor</b>	>0.90
<b>Frequency</b>	50 / 60 Hz
<b>Operating Temperature Pracovná teplota</b>	45°C
<b>Driver Type / Typ napájača</b>	Constant Current (CC)
<b>Product Dimension (mm) Rozmer svietidla (mm)</b>	A x B x C 595x595x28
<b>Luminaire Net Weight Hmotnosť svietidla</b>	2.2kg
<b>Material</b>	<b>Housing / teleso</b> Aluminum Alloy / hliníková zliatina
	<b>Diffuser / difuzor</b> PMMA / Polymetylmetakrylát
<b>Fixture Color / Farba svietidla</b>	White / Biela
<b>IP Rating / Krytie IP</b>	IP40
<b>Life Time / životnosť</b>	>50,000H (Ta=30°L80B10)
<b>Warranty / záruka</b>	5 Years/rokov

**Dimensions / Rozmery**

**Photometry**

**UNIT: cd**

- C0/180, 99.9 deg
- C30/210, 99.9 deg
- C60/240, 99.9 deg
- C90/270, 99.9 deg

AVERAGE BEAM ANGLE (50%): 99.9DEG